



CCTV CAMERA



2.5" COLOR DOME CAMERA



SPECIFICATION

Model No	BT-213/BT-213DN	BT-212/BT-212DN	BT-221/BT-221DN
Description	1/3" Color Dome Camera	1/3" Color Dome Camera	1/3" Color Dome Camera
Pick up Element	SONY HQ1	SONY SuperHAD	SHARP
Number of Pixels	<NTSC> 768(H) x 494(V) <PAL>752(H) X 582(V)	<NTSC> 510(H) x 492(V) <PAL>512(H) X 582(V)	<NTSC> 510(H) x 492(V) <PAL>512(H) X 582(V)
Back Light Compensation		ON	
Auto Electronics Shutter		ON	
ATW		ON	
AGC		ON	
Sync. Mode		Internal Sync.	
Scanning System		2:1 Interlance	
Resolution	540 TV Lines		420 TV Lines
S/N Ratio		More than 48dB	
Gamma		0.45	
Minimum Illumination	0.5 Lux, F1.4	0.5 Lux, F1.4	0.5 Lux, F1.4
Horizontal Sync Frequency	<NTSC> 15,734 KHz <PAL> 15,625 KHz	<NTSC> 15,734 KHz <PAL> 15,625 KHz	<NTSC> 15,734 KHz <PAL> 15,625 KHz
Video Output		1.0Vp-p, 75 ohm	
Power Source		DC 12V	
Power Consumption		6.6W	
Operating Temperature		-10°C to +60°C	
Lens Amount		3.6mm Board lens(Standard) 6/8/12/16mm (Optional)	
Shutter Control	<NTSC> 1/60-1/100,000 sec. <PAL> 1/50-1/100,000 sec	<NTSC> 1/60-1/100,000 sec. <PAL> 1/50-1/100,000 sec	<NTSC> 1/60-1/100,000 sec. <PAL> 1/50-1/100,000 sec
Dimension	85(ø) x 54(H) mm	85(ø) x 54(H) mm	85(ø) x 54(H) mm
Net Weight	0.135KG	0.135KG	0.135KG

* Specifications are subject to change without prior notice